

Staybond

MATERIAL SAFETY DATA SHEET

Product Class: Staybond Permanent Stud Lock

Name: T271

Item No.: 0104

Page 1 of 2

SECTION I - PRODUCT IDENTIFICATION

HMIS Codes **H** **F** **R**
 1 1 1

Sold by: Staybond Corp.
2103 Route 9 P. O. Box 428
Clifton Park, NY 12065-0428

Phone: 518 899-3357

**CHEMTREC® 24 Hour
Emergency Phone:** 800 424-9300
Fax Number: 518 899-5280
Date Revised: 10/25 / 01

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION

Hazardous Components	CAS #	OSHA (PEL)	ACGIH (TLV)	%
Cumene Hydroperoxide ***	80-15-9	N/A	N/A	1-3
Amorphous Silica	112945-52-5	6mg/m3	10mg/m3	0.1-1
Dimethacrylate Ester	25852-47-5	N/A	N/A	65-75
Bisphenol A Fumurate Resin	39382-25-7	N/A	N/A	20-30
SACCHARIN	81-07-2	N/A	N/A	1-3
Polyethylene	9002-88-4	N/A	N/A	1-3
Organic Acid	Trade Secret	N/A	N/A	0.1-1

*** This component is listed as a SARA Section 313 Toxic Chemical ***

SECTION III - PHYSICAL DATA

Boiling Point	Higher than 300°F	Appearance	Red liquid
Vapor Density	N/A	Odor	Mild
Coating V.O.C.	N/A	Specific Gravity	1.10 @ 80° F
Material V.O.C.	12.0%; 132 g / l	Evaporation Rate	N/A
Solubility in water	Slight		

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point	150- 200°F	Method Used	Tag Closed cup
Flammable limits in air by volume- Lower	N/A	Upper	N/A
Extinguishing Media	Foam, CO2, Dry Chemicals		
Special Firefighting Procedures	Air mask and procedures for fighting chemical fires		
Unusal Fire Explosion Hazards	Irritating Organic Vapors		

SECTION V - REACTIVITY DATA

Stability	Stable	Hazardous Polymerization	Will not occur
Incompatibility	Strong oxydizing and reducing agents		
Hazardous Decomposition	None known		
Conditions to Avoid	Stable under normal conditions.		

Staybond Corp., 2103 Route 9, P. O. Box 428, Clifton Park, N.Y. 12065-0428 USA
Tel: 518 899-3357 Fax: 518 899-5280

Staybond

MATERIAL SAFETY DATA SHEET

Product Class: Staybond Permanent Stud Lock

Name: T271

Item No.: 0104

Page 2 of 2

SECTION VI - HEALTH HAZARD DATA

Inhalation Health Risks None
Skin Eye Contact Mild eye irritant
Skin Absorption Irritation, rash, discomfort: Estimated dermal LD50 more than 2000mg/kg
Ingestion Headache, nausea: Estimated oral LD50 more than 5000mg/kg
Health Hazards Acute Chronic May cause dermatitis on prolonged contact in sensitive individuals
Carcinogenicity NTP No **IARC Monographs** No **OSHA Regulated** No
Medical Conditions Generally Aggravated by Exposure Dermatitis
Emergency First Aid Procedures
Primary route of entry-skin. Inhalation: Remove victim to fresh air. Eyes: Flush with water for 15 minutes. Contact physician. Skin: wash with mild soap and water for 15 minutes. Contact a physician if irritation or other problems occur. Ingestion: If swallowed, get medical assistance. DO NOT INDUCE VOMITING.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in case Material is Released Spilled

Take up unrecoverable or contaminated product. Disposable tools and inert absorbent material are recommended. Transfer to closable container.

Waste Disposal Method

Dispose of in accordance with Federal, State and local waste disposal regulations. This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR 261. Not a RCRA hazardous waste.

Precautions to be Taken in Handling Storing

Store in cool location away from sunlight and other sources of heat, sparks and flame. Keep container closed when not in use.

Other Precautions

Use with adequate ventilation. Avoid contact with skin and eyes.

SECTION VIII - CONTROL MEASURES

Respiratory Protection N/A
Ventilation General
Protective Gloves Rubber or plastic
Eye Protection Safety glasses or goggles
Other Protective Clothing Equipment N/A
Work Hygienic Practices N/A

SECTION IX - REGULATORY INFORMATION

Per DOT (49 CFR 172) this material is Unrestricted for Domestic Ground Transport
Product contains Saccharin. However, no CA Prop 65 hazard warning is necessary if used as labeled.

IMPORTANT NOTICE:

To the best of our knowledge the information contained herein is accurate, obtained from sources believed to be accurate. Staybond Corporation makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Staybond Corporation assumes no responsibility for injury from the use of the product described herein. This information is offered solely for your consideration and interpretation.

Staybond Corp., 2103 Route 9, P. O. Box 428, Clifton Park, N.Y. 12065-0428 USA
Tel: 518 899-3357 Fax: 518 899-5280